



251 N. Main Street
 Clarendon, PA 16313
 (814) 726-1058
 www.agiindustriespa.com

SAFEWAY TRENCH BOX: 4" HEAVY-DUTY DOUBLE WALL SERIES

Safety Is Our Business!

FEATURES & BENEFITS


- Designed and certified by a registered professional engineer to meet or exceed OSHA 29 CFR – 1926, Subpart P standards
- Stackable
- Knife or square bottom edge
- Four round lifting points
- Safe assembly
- **FREE Competent Person Training & Certification** on OSHA Standards for Trench Excavation with purchase
- Spreaders available from 24" and up
- Purchase or Rent
- Rent-To-Own options available
- Multiple sizes available



Side View



Front View



Four Round Lifting Points



Strut Pin

AGI Industries' Steel **Safeway Trench Box** will help ensure the safety of your employees while maintaining your compliance with OSHA Standards and laws.

Model	Height	Length	Pipe Clearance	*Shield Capacity (PSF)	**Shield Weight (Lbs)	Maximum Depth of Excavation per Soil Type			
						Type A – 25 PSF	Type B – 45 PSF	Type C – 60 PSF	Type C – 80 PSF
AGI40610H	6' 2"	10'	40"	1900	4530	76'	42.2'	31.7'	23.8'
AGI40612H	6' 2"	12'	40"	1900	5250	76'	42.2'	31.7'	23.8'
AGI40812H	8' 2"	12'	64"	1600	6420	64'	35.6'	26.7'	20'
AGI40816H	8' 2"	16'	64"	1540	9200	61.6'	34.2'	25.7'	19.3'

Not applicable to soft clays, free flowing materials, or organic peats

* PSF (Pounds Per Square Foot) rating provides the maximum shield capacity. Determine actual surcharge and soil pressures and consult tabulated data

** Shield weight includes two shields and no spreader struts