



251 N. Main Street
Clarendon, PA 16313
(814) 726-1058
www.agiindustriespa.com

SAFEWAY TRENCH BOX: 6" HEAVY-DUTY DOUBLE WALL SERIES

Safety Is Our Business!

FEATURES & BENEFITS


- Designed and certified by a registered professional engineer to meet or exceed OSHA 29 CFR – 1926, Subpart P standards
- Stackable
- Knife or square bottom edge
- Four round lifting points
- Safe assembly
- **FREE Competent Person Training & Certification** on OSHA Standards for Trench Excavation with purchase
- Spreaders available from 24" and up
- Purchase or Rent
- Rent-To-Own options available
- Multiple sizes available



Side View



Front View



Four Round Lifting Points



Strut Pin

AGI Industries' Steel **Safeway Trench Box** will help ensure the safety of your employees while maintaining your compliance with OSHA Standards and laws.

Model	Height	Length	Pipe Clearance	*Shield Capacity (PSF)	**Shield Weight (Lbs)	Maximum Depth of Excavation per Soil Type			
						Type A – 25 PSF	Type B – 45 PSF	Type C – 60 PSF	Type C – 80 PSF
AGI60820H	8' 2"	20'	64	1550	11,724	62'	34.4'	25.8'	19.3'

Not applicable to soft clays, free flowing materials, or organic peats

* PSF (Pounds Per Square Foot) rating provides the maximum shield capacity. Determine actual surcharge and soil pressures and consult tabulated data

** Shield weight includes two shields and no spreader struts